



Screw Base E26 / E27






GU-24 Base










Direct Wire




Curved Trim



Flat Trim



**Aluminum Surface with Trim Color:**



**Line Voltage**

120V, 220V, 277V line current

**DL5/DL6**

160 degree beam

Medium screw base: E26, E27 / GU-24 Pin base\*

\*California Title 24 requirement

**DLX**

160 degree beam

Direct Wire

**50,000 hour rated life**

**Down Light LED**

14 Watt typical

**Light Output**

700 Lumen (useful)

**Indoor**  
dry locations

**White (3) Color Temperatures:**

Warm White (2700K)

Neutral White (3500K)

Cool White (4500K)



**3-Year Warranty**

**Housing:**

Fits in 5" or 6" recessed IC or non-IC housings

**Fixtures:**

Residential and Commercial Recessed Fixtures

**Weight:**

1 lb

**Performance:**

*enLux RGB LED Light for general illumination is powered by its proprietary Solid State C.O.B Light Engine coupled with its unique patented thermal management components providing high efficacy and maximum energy efficiency - 14 Watts typical.*



*The enLux DL Down Light aluminum housing is finished in an ultra durable top coat. Safe, cool to touch, 100% recyclable (no mercury or hazardous materials\*\*).*

*\*\*California Title 22 compliant*



**DL Down Light Photometrics**

0 ft	Illuminance Distribution Ratio					
3 ft	0.379	0.385	0.408	0.483	0.711	1.000
6 ft	0.109	0.121	0.142	0.178	0.225	0.250
9 ft	0.059	0.068	0.079	0.093	0.105	0.111
12 ft	0.039	0.044	0.050	0.056	0.061	0.063
15 ft	0.028	0.031	0.035	0.037	0.039	0.040
	15 ft	12 ft	9 ft	6 ft	3 ft	CL



**DL Illuminance at Beam Centerline**

White	CCT	P/N	Total Lumen	Throw Distance (feet)				
				3	6	9	12	15
Warm	2700°K	591XXX	650	263.0	65.7	29.2	16.4	10.5
Neutral	3500°K	593XXX	675	271.4	67.8	30.2	17.0	10.9
Cool	4500°K	594XXX	700	280.9	70.2	31.2	17.6	11.2

Unit in lux  
1 lux = 0.0929 footcandle (fc)

**DL Product Code**

Product	CCT / Color	Can Size	Voltage	Trim Type	Trim Color	Reflector
<b>White Light</b>						
5	91 Warm (2700°K)	0 No Can Lead Wire	2 220V	0 Wide Curved	WF White Paint (Flat)	N None
	93 Neutral (3500°K)	2 5" Can Lead Wire	4 120V	1 Wide Flat	BF Black Paint (Flat)	C Clear
	94 Cool (4500°)	3 6" Can Lead Wire	7 277V	2 Tapered Cone	WG White Paint (Gloss)	G Gold
		4 4" Can E26/27		3 Tapered Baffle	BG Black Paint (Gloss)	H Haze
		5 5" Can E26/27			CA Clear Anodized	P Pewter
		6 6" Can E26/27			BA Black Anodized	
		7 4" Can GU24			SC Satin Chrome	
		8 5" Can GU24			AB Aged Bronze	
		9 6" Can GU24				
<b>Standard Color</b>						
5	16 Red (620nm)	0 No Can Lead Wire	2 220V	0 Wide Curved	WF White Paint (Flat)	N None
	17 Amber (589nm)	2 5" Can Lead Wire	4 120V	1 Wide Flat	BF Black Paint (Flat)	C Clear
	18 Green (535nm)	3 6" Can Lead Wire	7 277V	2 Tapered Cone	WG White Paint (Gloss)	G Gold
	19 Blue (465nm)	4 4" Can E26/27		3 Tapered Baffle	BG Black Paint (Gloss)	H Haze
		5 5" Can E26/27			CA Clear Anodized	P Pewter
		6 6" Can E26/27			BA Black Anodized	
		7 4" Can GU24			SC Satin Chrome	
		8 5" Can GU24			AB Aged Bronze	
		9 6" Can GU24				
<b>Custom Color</b>						
5	20 415nm	0 No Can Lead Wire	2 220V	0 Wide Curved	WF White Paint (Flat)	N None
	23 Vita Yellow	2 5" Can Lead Wire	4 120V	1 Wide Flat	BF Black Paint (Flat)	C Clear
	24 2050°K	3 6" Can Lead Wire	7 277V	2 Tapered Cone	WG White Paint (Gloss)	G Gold
	28 Margaritas Pink	4 4" Can E26/27		3 Tapered Baffle	BG Black Paint (Gloss)	H Haze
		30 Restaurant Pink	5 5" Can E26/27		CA Clear Anodized	P Pewter
		31 Pink Magenta	6 6" Can E26/27		BA Black Anodized	
		34 Deep Purple	7 4" Can GU24		SC Satin Chrome	
		36 Congo Blue	8 5" Can GU24		AB Aged Bronze	
		37 Happy Blue	9 6" Can GU24			

**Examples**

591641-WF-N	DL Down Light	Warm White	6" Can	120V	Wide Flat	White Paint (Flat)	No reflector
593522-BG-G	DL Down Light	Neutral White	5" Can	220V	Tapered Cone	Black Paint (Gloss)	Gold Reflector

